



(800)823-0182 / www.SNAsportsgroup.com

Specifications for Carbon EDGE

MODEL NO. SNAVB72

Carbon EDGE Uprights shall consist of an external 3" outside diameter, 1/4" wall high modulus carbon fiber wound composite tube and a 2 1/2" outside diameter high modulus carbon fiber wound composite telescoping inner pole. Inner pole shall move freely up and down to adjustment heights between 6' 4" and 8' 2". Uprights shall feature pin stop height settings along with intermediate settings for added versatility. Net tensioning device shall be mounted on the post, and shall be a 26:1 ratio worm-gear in which all shafts rotate in sealed ball bearings. Winch shall have a non-removable folding handle, and shall tension an attached 2" wide nylon-webbing strap. Posts are supplied with Velcro-on D-straps to attach bottom net connections, and an adjustable foot on each post allows for fine-tuning of net height. Winch Post to weigh 22#, and End Post to weigh 17#. Adapters to allow installation into 3 1/2" and 4" sockets shall be available at no extra cost. Standards and winch shall carry no less than a limited lifetime warranty. Entire system shall meet or exceed all NCAA, USVBA, and NFHS requirements for competition.

MODEL NO. SNAVB722

Carbon EDGE Center Post shall consist of a single upright – as described above – with winch on one side, and net connections on the opposite. Using this post in the middle of a standard net system will allow for a two (2) net set-up using only 3 uprights. All warranties from above apply.

VOLLEYBALL FLOOR SLEEVE AND COVER PLATE

MODEL NO. VB23

Aluminum sleeve shall be 9" long. Inside diameter of the sleeve shall be 3". Floor plate shall be the model VB23CV. Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only; allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6-31/32" in diameter. Diameter of clear opening shall be 6".

KEVLAR OUTDOOR VOLLEYBALL NET

MODEL NO. SNAVB1250K

Totally encased stretcher bars on each side of 32 foot net. Net shall be one meter wide, and squares shall be knotless woven webbing. Net shall have 45' x 1/4" no-stretch Kevlar top rope and 45' braided Tenex bottom rope, and white vinyl top, bottom, and side tapes. Four (4) Velcro tensioners supply horizontal tensioning of netting. Rope Ratchet Tensioner to supply bottom rope tension is included. May require field shortening of top and/or bottom rope. Meets or exceeds all NCAA, USVBA, and NFHS rules and requirements.

NET ANTENNAE WITH SIDELINE MARKERS

MODEL NO. SNAVB12

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.

CABLE COVERS

MODEL NO. VB35P

Cable covers shall be made of 1/2" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.

UPRIGHT SAFETY PADS

MODEL NO. SNAVB51P

Each upright pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to uprights shall be effected by Velcro straps. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.



(800)823-0182 / www.SNAsportsgroup.com

CENTER UPRIGHT SAFETY PADS

MODEL NO. VB510P

Same specifications exist as the model SNAV51P upright pad. Exception: each center upright pad shall consist of two identical pieces, 72" in height and 10.5" in width. Attachment to the uprights shall be effected by Velcro straps that are attached on both pads. 18 colors available.

VB73A REFEREE STAND WITH PADS

MODEL NO. VB73A

Shall be of tubular steel construction with steel platform. Stand shall attach to the upright by means of a heavy-duty steel clamp with rubber pads to protect the upright. Clamp shall close by means of a threaded rod-driven mechanism, and shall fold away when not in use. Stand shall have wheels to allow for easy transport, and shall have non-slip rubber floor pads. Stand shall have adjustable legs allowing for platform adjustments from 47" to 53". **Available in Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue padding.**

VB76 FREESTANDING FOLDING REFEREE STAND

MODEL NO. VB76

Shall be of tubular steel construction with steel platform. Shall be completely freestanding, with rear wheels for transport. Stand shall be able to fold together for ease of storage and transport. Dimensions shall be 36" L x 27.5" W x 7' 4" in height. Padding for the legs and platform shall be of dense foam body covered with nylon-reinforced vinyl. **Available in Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue.**

DELUXE 6-POST EQUIPMENT CART

MODEL NO. VB96

Shall be of tubular steel construction with two vinyl tarp storage areas for nets and antennas. Cart will accommodate 6 posts and have the capability to hold posts with pads on them. Top of cart shall accommodate storage of Schelde Referee Stand with pads. Gross dimensions of cart shall be 46" high, 32 ½" wide, and 41 17-32" long.

4-POST EQUIPMENT CART

MODEL NO. VB94

Shall be of tubular steel construction with metal platform for accessories. Cart will accommodate 4 posts and have the capability to hold posts with pads on them. Gross dimensions of cart shall be 42" high x 32" wide x 46" long.

VOLLEYBALL T-BASE

MODEL NO. VBTBASE

Designed for use in facilities where the sub-floor structure is not adequate to accommodate the installation of a floor sleeve.

T-Base shall be constructed of welded steel capable of accepting a 4" diameter volleyball post. The gross dimensions will be 12" H x 17 ¾"L x 18"W. The base is securely locked in place with a ½" turn bolt screwed into a ½" diameter, 13 thread-per-inch floor anchor.

T-BASE PADDING

MODEL NO. VBTBASEP

Each T-Base pad shall be two pieces – one wrap-around pad for T-Base sides, and one trapezoidal pad for T-Base top. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to each other shall be effected by Velcro. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.