



## **Specifications for Collegiate Sand Pro System (C4SAND)**

### **MODEL NO. SNASVB40C4**

Removable type for Positive-Lock sleeves. Uprights shall be one single piece, 115" long and anodized 6061-T6 aluminum, 3-15/16" in diameter, weighing 21 and 28 lbs. Net shall attach to the sliding End Rail, which shall be mounted in profiled grooves running infinitely over the full range. Net shall attach to the sliding Winch Rail, which shall be mounted in profiled grooves running infinitely over the full range. Net tensioning device shall be mounted on the Winch Rail, and shall be a low profile, threaded rod-type non-slip worm drive linear-actuator type, utilizing conical toothed steel gears for safety and durability. The range of this gear mechanism shall be 17-1/2". Gear mechanism shall be completely encased in anodized aluminum. A two position (lock/off) lever lock shall be used to provide slip-free adjustment of the net height; screw-in adjustment knobs shall be deemed unacceptable. Uprights shall adjust to allow for Men, Women, and Juniors heights. Uprights shall have protective molded plastic caps, and all hardware shall be weather-resistant to allow for both indoor and outdoor sand applications. Standards and winch shall carry no less than a limited lifetime warranty. Entire system shall meet or exceed all NCAA and USVBA requirements for competition.

### **POSITIVE-LOCK REMOVABLE SAND FLOOR SLEEVE**

#### **MODEL NO. SVB27**

Steel sleeve shall be 18" long. Inside diameter of the sleeve shall be 4". Unique Positive-Lock design shall allow for sleeve to be removed from a permanent concrete foundation with embedded base plate with a simple twist by means of three (3) keyhole slots along enlarged, 1/2" thick sleeve bottom. Sleeve shall be stainless steel to withstand outdoor applications if left in place. Base plate shall be 1/2" thick stainless steel with 3 permanently-welded solid steel anchor posts, and shall be seated into the concrete footing by means of four (4) 9/16" x 15" angled solid steel bolts.

### **OFFICIAL BEACH VOLLEYBALL NET**

#### **MODEL NO. SNASVB28**

Net shall be 28 feet in length and 1-meter maximum width official size. Wide side tapes and top/bottom tapes in 18oz vinyl. Extra strong #36 nylon polyester treated 4" square, knotted netting shall wrap around dowels. 1-1/8" wooden dowels for end pockets, and strong nylon tie cords. 5/32" top cable and 1/8" bottom cable.

### **VOLLEYBALL COURT BOUNDARY MARKER**

#### **MODEL NO. SVB6200**

For sand or grass courts. Made of 2" wide woven web straps. Pre-measured with corner loops, stakes and tension cords for quick set up. Durable roll up reel for easy storage. For official size courts, and fully adjustable to any court size. Color Black.

### **UPRIGHT SAFETY PADS**

#### **MODEL NO. SNAVB51P**

Each upright pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to uprights shall be effected by Velcro straps. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark, Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.

*The following items are optional for the outdoor system:*

### **SAND VOLLEYBALL REFEREE STAND WITH PADS**

#### **MODEL NO. SVB73**

Shall be of tubular steel construction with steel platform. Stand shall attach to the upright by means of a heavy-duty steel clamp with rubber pads to protect the upright. Clamp shall close by means of a threaded rod-driven mechanism, and shall fold away when not in use. Stand shall have sand skid platforms instead of wheels to prevent sinking into sand surface. **Available in Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue.**



#### **CABLE COVERS**

**MODEL NO. VB35P**

Cable covers shall be made of ½" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.

#### **NET ANTENNAE WITH SIDELINE MARKERS**

**MODEL NO. SNAVB12**

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 ½" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.