



(800)823-0182 / www.SNAsportsgroup.com

Specifications for Telescopic Pro II

MODEL NO. SNAVB12TP4

Uprights shall consist of an external 3-15/16" outside diameter, anodized aluminum tube and a 3" outside diameter 6061-T6 aluminum telescoping clear anodized inner pole. Inner pole shall move freely up and down to adjustment heights between 6' 6" (storage position) and 8' 2" assisted by an internal spring mechanism to ease adjustment. Upright shall feature pin stop height settings at Men, Women, and Juniors along with intermediate settings added at two inches above Men and Women, and two inches below Juniors. Upright shall feature a sliderail mounted to the inner post which will achieve differing net heights as the spring-loaded inner post moves. Inner post movement shall be spring-assisted. Net tensioning device shall be mounted on the sliderail, and shall be a low profile, threaded rod-type non-slip worm drive linear-actuator type, utilizing conical toothed steel gears for safety and durability. The range of this gear mechanism shall be 17 1/2". Mechanism and threaded rod shall be encased in anodized aluminum. A height adjustment foot shall be permanently attached to the bottom of the external composite tube to allow installation into any 4" diameter floor socket. Adapters to allow installation in 3" and 3.5" sockets shall be available at no additional cost. Standards and winch shall carry no less than a limited lifetime warranty. Entire system shall meet or exceed all NCAA, USVBA, and NFHS requirements for competition.

MODEL NO. SNAVB12TP4W

Telescopic Pro Center Post shall consist of a single upright – as described above – with winch on one side, and net connections on the opposite. Using this post in the middle of a standard net system will allow for a two (2) net set-up using only 3 uprights. All warranties from above apply.

VOLLEYBALL FLOOR SLEEVE

MODEL NO. VB27FS

Aluminum sleeve shall be 13" long. Inside diameter of the sleeve shall be 4".

UNIVERSAL HINGED BRASS COVER PLATE

MODEL NO. VB23CV

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

MODEL NO. VB27

This package shall include both the VB27FS floor sleeve and VB23CV cover plate listed above.

INTERNATIONAL NET WITH RATCHET TENSIONER

MODEL NO. SNAVB1298A

Net shall be 9.8 meters in length and 1-meter maximum width. Netting shall be 10 centimeters square mesh, black nylon, KNOTLESS. Wide side tapes with sewn-in wooden dowels for equal net tension. Top cable shall be 1/8" steel, specially sewn into 50-millimeter white nylon binding. Bottom tension rope shall be nylon, covered by 30-millimeter white nylon binding.

NET ANTENNAE WITH SIDELINE MARKERS

MODEL NO. SNAVB12

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.

CABLE COVERS

MODEL NO. VB35P

Cable covers shall be made of 1/2" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.



(800)823-0182 / www.SNAsportsgroup.com

UPRIGHT SAFETY PADS

MODEL NO. SNAVB51P

Each upright pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to uprights shall be effected by Velcro straps. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.

CENTER UPRIGHT SAFETY PADS

MODEL NO. VB510P

Same specifications exist as the model SNAVB51P upright pad. Exception: each center upright pad shall consist of two identical pieces, 72" in height and 10.5" in width. Attachment to the uprights shall be effected by Velcro straps that are attached on both pads. 18 colors available.

VB73A REFEREE STAND WITH PADS

MODEL NO. VB73A

Shall be of tubular steel construction with steel platform. Stand shall attach to the upright by means of a heavy-duty steel clamp with rubber pads to protect the upright. Clamp shall close by means of a threaded rod-driven mechanism, and shall fold away when not in use. Stand shall have wheels to allow for easy transport, and shall have non-slip floor pads. Stand shall have adjustable legs allowing for platform adjustments from 47" to 53.

Available in Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue padding.

VB76 FREESTANDING FOLDING REFEREE STAND

MODEL NO. VB76

Shall be of tubular steel construction with steel platform. Shall be completely freestanding, with rear wheels for transport. Stand shall be able to fold together for ease of storage and transport. Dimensions shall be 36" L x 27.5" W x 7' 4" in height. Padding for the legs and platform shall be of dense foam body covered with nylon-reinforced vinyl. **Padding shall be Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue.**

DELUXE 6-POST EQUIPMENT CART

MODEL NO. VB96

Shall be of tubular steel construction with two vinyl tarp storage areas for nets and antennas. Cart will accommodate 6 posts and have the capability to hold posts with pads on them. Top of cart shall accommodate storage of Schelde Referee Stand with pads. Gross dimensions of cart shall be 46" high – 32 1/2" wide – 41 17/32" long.

4-POST EQUIPMENT CART

MODEL NO. VB94

Shall be of tubular steel construction with metal platform for accessories. Cart will accommodate 4 posts and have the capability to hold posts with pads on them. Gross dimensions of cart shall be 42" high x 32" wide x 46" long.



(800)823-0182 / www.SNAsportsgroup.com

VOLLEYBALL T-BASE

MODEL NO. VBTBASE

Designed for use in facilities where the sub-floor structure is not adequate to accommodate the installation of a floor sleeve.

T-Base shall be constructed of welded steel capable of accepting a 4" diameter volleyball post. The gross dimensions will be 12" H x 17 ¾"L x 18"W. The base is securely locked in place with a ½" turn bolt screwed into a ½" diameter, 13 thread-per-inch floor anchor.

T-BASE PADDING

MODEL NO. VBTBASEP

Each T-Base pad shall be two pieces – one wrap-around pad for T-Base sides, and one trapezoidal pad for T-Base top. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to each other shall be effected by Velcro. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Navy Blue, Dark Royal, Purple, Gray, Brown, Pink, and Black.