



1. TYPICAL CONSTRUCTION MATERIALS:
MASONRY BLOCK OR POURED CONCRETE
2. GATES ARE REQUIRED FOR ALL INSTALLATIONS
GATES SHALL BE MOUNTED ON METAL POSTS IMBEDDED IN CONCRETE AT CORNERS, NOT ATTACHED TO CORNERS
METAL FRAMED WITH CHAINLINK AND COLORED SLATES
GATES SHALL OPEN 170 DEGREES MINIMUM
GATES SHALL LOCK IN EITHER OPEN OR CLOSED POSITIONS
3. SURFACE - CONCRETE LEVEL
CONCRETE MINIMUM THICKNESS OF 4" ON 4" AGGREGATE BASE
SURROUNDING PAVED AREA LEVEL WITH ENCLOSURE
4. STOPS TO PREVENT DUMPSTER FROM HITTING WALLS WHEN MOVING IN AND OUT SHALL BE PROVIDED.
5. SLOPE FROM THE FRONT OF THE TRASH ENCLOSURE SHALL BE A MINIMUM OF 2% AND MAXIMUM OF 4%.
6. ENCLOSURE HEIGHT SHALL BE 72 INCHES.
7. ANY REQUIRED DRAINAGE SHALL NOT INTERFERE WITH MOVEMENT OF THE DUMPSTER.
8. CLEAR ACCESS EQUAL TO THE SIZE OF THE ENCLOSURE, BUT NOT LESS THAN 8'X10' MUST BE MAINTAINED IN FRONT OF THE ENCLOSURE AT ALL TIMES.
9. ENCLOSURES ARE FOR THE EXPRESS USE OF CONTAINING DUMPSTER'S, NO OTHER USES ARE PERMITTED.



STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION

STANDARD DUMPSTER ENCLOSURE

SECTION TOWN OF GARDNERVILLE

RELEASE DATE: 2/1/09

DWG: TOG-07