9' RoofGuard Rooftop Guardrail Kit F SUPPLY INC. 3412 49th Street North Saint Petersburg, FL 33710



FACTORY SUPPLY INC.

Leading Edge

This rooftop quardrail system provides 9 feet of leading edge fall protection, requires no rooftop penetration, and can be categorized as a passive fall protection solution.

Eliminate Active Fall Protection Equipment

With the addition of this fall protection system you will be able to eliminate the need for active fall protection equipment such as Safety Harnesses/ Lanyards, Roof Anchor Systems or Horizontal Lifelines. Meaning you will not have to worry about any fines for compliance violations from having inadequate or non-existent rooftop safety training or products.



Storage

These systems come pre-engineered in a singular crate; most parts are pre-assembled with simple to follow instructions and a singular tool for installation.

Usage

This fall protection system is ideal for providing a reliable fall safety device around HVAC, Vents, near Access Ladders, Antennas, Valves, Solar Panels, or simply near frequently travelled areas that require routine maintenance.

Free-Standing

Our free-standing, portable, modular systems are constructed with corrosion resistant, lightweight aluminum tubing and utilize counter weighted baseplates, no roof penetration is required meaning your roof remains intact.





Technical Specifications



Part Number	Height	Crate Dimensions	Customizable
RGC-KIT-09	42" from Ground to Top of Top-Rail	9'-4" x 15" x 18"	Yes
Accessories	Rails Width	Length from Edge to Back of Baseplates	Weight
RG-PAD	9' 4", With Baseplates: 9'6"	7'8"	450 lbs
Certifications	Diameter of Rail	What Comes in the Kit	Baseplates
This system is designed in order to meet or exceed all major governing bodies fall protection requirements including: ANSI, OSHA, OHSA and MOL, these include OSHA Standard 29 CFR 1926.501, 29 CFR 1926.502, Canadian National Building Code 4.1.10.1(1) (e), 4.1.10.1(2), 4.1.10.1(4), Ontario Building Code Section 4.1.10.1(1)(b), 4.1.10.1(2), 4.1.10.1(4), HSG-33 Health & Safety in Roof Work, BS 6399: Part 2 1995 Wind Code, EU Directives & CDM Regulations, BGV A1: 2000, Health, Safety & Welfare Regulation 13 "Falls or Falling Objects" 1992	1.9" OD Aluminum Pipe	Single tool supplied for assembly, complete installation manual and layout drawings, 8 counter weighted baseplates, 4 rubber mats to protect the rooftop membrane, 4 pre-assembled vertical posts, 6 horizontal rails, set screws	Self-weighted bases are portable and allow simple, non-penetrating installation to the rooftop.





Request a Quote



Save your form and email it to your sales representative or sales@factorysupply.com or print and fax it to +1 (727) 347-4830

Quotation Type

Budgetary (project funding) Firm (funded project)

Time Frame (When Do You Require Your Stand?)

Less Than 3 Months 3 to 6 Months 6 to 9 Months 9 to 12 Months Other

Customer Information

Company Name

Street Address State/Province

City Zip Code/Postal Code

Contact Name Phone
E-Mail Cell

Where Did You Hear About Us?

Email Campaign Social Media Search Engine i.e. Google Other

Additional Information

Please attach any related images or files to your email or fax.







